# **Safety Data Sheet**

Issue Date 01-Jun-2010 Revision Date: 02-Oct-2013 Version 1

# 1. IDENTIFICATION

**Product Identifier** 

Product Name ARROW 1104RB Low-VOC Solvent Cement for PVC Plastic Pipe

Other means of identification

SDS # AAC-1104RB

UN/ID No UN1133

Product Code 1104RB, AA-1104RB

Recommended use of the chemical and restrictions on use

Recommended Use Low-VOC solvent cement for PVC plastic pipe

# Details of the supplier of the safety data sheet

**Supplier Address** 

Arrow Adhesives Company 5457 Spalding Dr. Norcross, GA 30092

**Emergency Telephone Number** 

**Company Phone Number** 1-800-678-9058

Emergency Telephone (24 hr) INFOTRAC 1-800-535-5053 (North America) 1-352-323-3500 (International)

# 2. HAZARDS IDENTIFICATION

Appearance Clear liquid Physical State Liquid Odor Ether-like

# Classification

Acute toxicity - Oral	Category 4
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

## **Hazards Not Otherwise Classified (HNOC)**

May be harmful in contact with skin

#### Signal Word

Danger

## **Hazard Statements**

Harmful if swallowed

Causes serious eye irritation

Suspected of causing cancer

May cause respiratory irritation. May cause drowsiness or dizziness

Highly flammable liquid and vapor

ARROW 1104RB Low-VOC PVC Cement Revision Date: 02-Oct-2013



# **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear eye/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

# **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed Store locked up Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

# WHMIS Classification

Class B-Division 2 Class D-Division 2A Class D-Division 2B

## **Other Hazards**

Harmful to aquatic life with long lasting effects

## **Unknown Acute Toxicity**

8% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Tetrahydrofuran	109-99-9	Proprietary
Methyl ethyl ketone	78-93-3	Proprietary
Cyclohexanone	108-94-1	Proprietary
Acetone	67-64-1	Proprietary
PVC Resin	9002-86-2	Proprietary

<sup>\*</sup> The exact percentage (concentration) of composition has been withheld as a trade secret

## 4. FIRST-AID MEASURES

## **First Aid Measures**

**General Advice** If exposed or concerned: Get medical advice/attention.

Eye Contact In case of irritation from airborne exposure, move to fresh air. Rinse immediately with plenty

of water, also under the eyelids, for at least 15 minutes. Seek immediate medical

Revision Date: 02-Oct-2013

attention/advice.

**Skin Contact**Take off contaminated clothing. Wash with soap and water. If symptoms persist, call a

physician. Wash contaminated clothing before reuse.

**Inhalation** Remove to fresh air. If symptoms persist, call a physician. If breathing is difficult, give

oxygen. Seek immediate medical attention/advice.

**Ingestion** Rinse mouth. Seek medical attention. If drowsy or unconscious, do not give anything by

mouth; place individual on the left side with head down. Do not induce vomiting.

# Most important symptoms and effects

**Symptoms** Exposed individuals may experience eye tearing, redness and discomfort. Prolonged or

repeated skin contact may result in dermatitis (red, dry skin). May cause nose and throat irritation, with possible central nervous system effects. Fatigue and weakness. May cause drowsiness or dizziness. Long term overexposure may cause liver and kidney damage.

# Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Individuals with chronic respiratory, skin, kidney, or liver disorders

may be at increased risk from exposure.

# 5. FIRE-FIGHTING MEASURES

## **Suitable Extinguishing Media**

Foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable Extinguishing Media Not determined.

# Specific Hazards Arising from the Chemical

Class IB Flammable Liquid. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products Carbon oxides. Various hydrocarbon vapors and toxic gases.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required. ELIMINATE all ignition sources (no

smoking, flares, sparks or flames in immediate area). Persons not wearing proper personal

Revision Date: 02-Oct-2013

protective equipment should be excluded from area of spill.

**Environmental Precautions**Do not allow into any sewer, on the ground or into any body of water. See Section 12 for

additional Ecological Information.

#### Methods and material for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Clean-Up** Pump or vacuum transfer spilled product to clean containers for recovery. Absorb

unrecoverable product. Transfer contaminated absorbent, soil and other materials to

containers for disposal.

## 7. HANDLING AND STORAGE

## Precautions for safe handling

Advice on Safe Handling Wash thoroughly after handling. Use personal protection recommended in Section 8. Do

not eat, drink or smoke when using this product. Avoid breathing vapors or mists. Use only in well-ventilated areas. Ground/bond container and receiving equipment. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, solid) all hazard precautions given in the data sheet must be

observed. Avoid prolonged contact with eyes, skin, and clothing. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

# Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store containers

upright. Store away from heat, sparks, flame.

Incompatible Materials Oxidizers. Acids. Bases.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Tetrahydrofuran	STEL: 100 ppm	TWA: 200 ppm	IDLH: 2000 ppm
109-99-9	TWA: 50 ppm	TWA: 590 mg/m <sup>3</sup>	TWA: 200 ppm
	S*	(vacated) TWA: 200 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 590 mg/m <sup>3</sup>	STEL: 250 ppm
		(vacated) STEL: 250 ppm	STEL: 735 mg/m <sup>3</sup>
		(vacated) STEL: 735 mg/m <sup>3</sup>	
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	-
		(vacated) STEL: 2400 mg/m <sup>3</sup>	
		The acetone STEL does not apply	
		to the cellulose acetate fiber	
		industry. It is in effect for all other	
		sectors	
		(vacated) STEL: 1000 ppm	
Methyl ethyl ketone	STEL: 300 ppm	TWA: 200 ppm	IDLH: 3000 ppm
78-93-3	TWA: 200 ppm	TWA: 590 mg/m <sup>3</sup>	TWA: 200 ppm
		(vacated) TWA: 200 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 590 mg/m <sup>3</sup>	STEL: 300 ppm
		(vacated) STEL: 300 ppm	STEL: 885 mg/m <sup>3</sup>
		(vacated) STEL: 885 mg/m <sup>3</sup>	-
Cyclohexanone	STEL: 50 ppm	TWA: 50 ppm	IDLH: 700 ppm
108-94-1	TWA: 20 ppm	TWA: 200 mg/m <sup>3</sup>	TWA: 25 ppm
	S*	(vacated) TWA: 25 ppm	TWA: 100 mg/m <sup>3</sup>
		(vacated) TWA: 100 mg/m <sup>3</sup>	
		(vacated) S*	
PVC Resin	TWA: 1 mg/m <sup>3</sup> respirable fraction	-	-
9002-86-2			

## **Appropriate engineering controls**

**Engineering Controls** Apply technical measures to comply with the occupational exposure limits. Ventilation

systems. Eyewash stations. Showers.

# Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Splash goggles or safety glasses.

**Skin and Body Protection** Rubber gloves. Use body protection appropriate for task.

**Respiratory Protection** Not required under normal conditions. If recommended levels are exceeded, respiratory

protection must be selected to assure compliance with OSHA Standard 29CFR 1910.134.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical State Liquid

AppearanceClear liquidOdorEther-likeColorClearOdor ThresholdNot determined

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH Not available
Melting Point/Freezing Point Not determined
Boiling Point/Boiling Range 56 °C / 133 °F
Flash Point -20 °C / -4 °F

**Evaporation Rate** > 1.0 (butyl acetate = 1)

Flammability (Solid, Gas) n/a-liquid
Upper Flammability Limits 12.8%
Lower Flammability Limit 1.8%
Vapour Pressure 190 mm Hg

Vapour Pressure 190 mm Hg @ 20°C (68°F)

Vapor Density 2.5 (Air=1)

**Specific Gravity** 0.900 **Water Solubility** Negligible Solubility in other solvents Not determined **Partition Coefficient** Not determined **Auto-ignition Temperature** Not determined **Decomposition Temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

VOC Content Maximum VOC emissions when applied and tested per SCAQMD Rule 1168, Test Method

316A is <= 510 g/L

# 10. STABILITY AND REACTIVITY

#### Reactivity

Not reactive under normal conditions.

# **Chemical Stability**

Stable under recommended storage conditions.

#### **Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous Polymerization** Hazardous polymerization does not occur.

#### **Conditions to Avoid**

Avoid heat, sparks, open flames and other ignition sources.

#### **Incompatible Materials**

Oxidizers. Acids. Bases.

# **Hazardous Decomposition Products**

Carbon oxides. Hydrogen chloride. Other various hydrocarbons.

# 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

**Product Information** 

**Eye Contact** Causes serious eye irritation.

**Skin Contact** May be harmful in contact with skin.

Inhalation Avoid breathing vapors or mists.

Ingestion Harmful if swallowed.

# **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Tetrahydrofuran	= 1650 mg/kg (Rat)	-	= 53.9  mg/L ( Rat ) 4 h = 180 mg/L
109-99-9			( Rat ) 1 h
Acetone 67-64-1	= 5800 mg/kg ( Rat )	-	-
Methyl ethyl ketone 78-93-3	= 2737 mg/kg ( Rat )	= 6480 mg/kg ( Rabbit )	-
Cyclohexanone 108-94-1	= 800 mg/kg ( Rat )	= 948 mg/kg ( Rabbit )	= 10.7 mg/L (Rat) 4 h = 8000 ppm (Rat) 4 h

## Information on physical, chemical and toxicological effects

**Symptoms** Please see section 4 of this SDS for symptoms.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

However, the product as a whole has not been tested.

Chemical Name	ACGIH	IARC	NTP	OSHA
Tetrahydrofuran 109-99-9	А3			
Cyclohexanone 108-94-1	А3	Group 3		
PVC Resin 9002-86-2		Group 3		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

**Numerical measures of toxicity** 

Not determined

**Unknown Acute Toxicity** 8% of the mixture consists of ingredient(s) of unknown toxicity.

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

Harmful to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Tetrahydrofuran		1970 - 2360: 96 h		5930: 24 h Daphnia magna
109-99-9		Pimephales promelas mg/L		mg/L EC50
		LC50 flow-through 2700 -		
		3600: 96 h Pimephales		
		promelas mg/L LC50 static		
Acetone		4.74 - 6.33: 96 h	EC50 = 14500 mg/L 15 min	
67-64-1		Oncorhynchus mykiss mL/L		magna mg/L EC50 Static
		LC50 6210 - 8120: 96 h		12600 - 12700: 48 h Daphnia
		Pimephales promelas mg/L		magna mg/L EC50
		LC50 static 8300: 96 h		
		Lepomis macrochirus mg/L		
		LC50		
Methyl ethyl ketone		3130 - 3320: 96 h	EC50 = 3403 mg/L 30 min	520: 48 h Daphnia magna
78-93-3		Pimephales promelas mg/L	EC50 = 3426 mg/L 5 min	mg/L EC50 5091: 48 h
		LC50 flow-through		Daphnia magna mg/L EC50
				4025 - 6440: 48 h Daphnia
				magna mg/L EC50 Static
Cyclohexanone	20: 96 h Chlorella vulgaris	481 - 578: 96 h Pimephales		800: 24 h Daphnia magna
108-94-1	mg/L EC50	promelas mg/L LC50 flow-	EC50 = 21.3 mg/L 10 min	mg/L EC50
		through 8.9: 96 h	EC50 = 25 mg/L 5 min	
		Pimephales promelas mg/L		
		LC50		

# Persistence/Degradability Not determined.

# Bioaccumulation Not determined.

# **Mobility**

Chemical Name	Partition Coefficient
Tetrahydrofuran 109-99-9	0.45
Methyl ethyl ketone 78-93-3	0.29
Cyclohexanone 108-94-1	0.86
Acetone 67-64-1	-0.24

# **Other Adverse Effects**

Not determined

# 13. DISPOSAL CONSIDERATIONS

## **Waste Treatment Methods**

**Disposal of Wastes**Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

# **US EPA Waste Number**

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Tetrahydrofuran 109-99-9				U213
Acetone 67-64-1		Included in waste stream: F039		U002
Methyl ethyl ketone 78-93-3	U159	Included in waste streams: F005, F039	200.0 mg/L regulatory level	U159
Cyclohexanone 108-94-1		Included in waste stream: F039		U057

# California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Tetrahydrofuran	Toxic
109-99-9	Ignitable
Methyl ethyl ketone	Toxic
78-93-3	Ignitable
Acetone	Ignitable
67-64-1	

# 14. TRANSPORT INFORMATION

**Note** Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances. Shipments of containers holding 1 liter or less in volume may qualify for a "Limited Quantity" exception. Refer to 49 CFR 173.150 for

additional information.

**DOT** 

UN/ID No UN1133
Proper Shipping Name Adhesives

Hazard Class 3
Packing Group ||

IATA

UN/ID No UN1133
Proper Shipping Name Adhesives

Hazard Class 3
Packing Group ||

**IMDG** 

UN/ID No UN1133
Proper Shipping Name Adhesives

Hazard Class 3
Packing Group ||

Marine Pollutant This material may meet the definition of a marine pollutant

# 15. REGULATORY INFORMATION

## **International Inventories**

TSCA Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

## US Federal Regulations

## **CERCLA**

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Tetrahydrofuran	1000 lb		RQ 1000 lb final RQ
109-99-9			RQ 454 kg final RQ
Methyl ethyl ketone	5000 lb		RQ 5000 lb final RQ
78-93-3			RQ 2270 kg final RQ
Cyclohexanone	5000 lb		RQ 5000 lb final RQ
108-94-1			RQ 2270 kg final RQ
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

#### **SARA 313**

Not determined

# **US State Regulations**

# **California Proposition 65**

This product may contain trace levels of chemicals known to the State of California to cause cancer. Exposure to these chemicals above the State of California 'No Significant Risk Level' is unlikely under normal use conditions.

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Tetrahydrofuran 109-99-9	X	X	X
Acetone 67-64-1	X	X	X
Methyl ethyl ketone 78-93-3	X	X	X
Cyclohexanone 108-94-1	X	X	X
PVC Resin 9002-86-2	X		

# **16. OTHER INFORMATION**

NFPA Health Hazards Flammability Instability Special Hazards

3 1 None

Revision Date: 02-Oct-2013

**HMIS** Health Hazards Flammability Physical Hazards Personal Protection

3 1 G

Issue Date01-Jun-2010Revision Date:02-Oct-2013Revision NoteNew format

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

\_\_\_\_\_\_