



PRODUCT DATA SHEET

1124

TRANSITION

ABS to PVC Medium Body Cement

DESCRIPTION

1124 is a solvent cement designed specifically for use in joining ABS (Acrylonitrile-Butadiene-Styrene) pipe or fittings to PVC (Poly Vinyl Chloride) pipe or fittings in transition joints between a ABS and PVC system with interference fit through 6" diameter (expect Sch. 80). It is a fast setting, high strength solvent cement. 1124 meets 'LOW-VOC' requirements, as outlined by SCAQMD 1168/316A.

APPLICATION

1124 is formulated for use on piping systems for DWV (drain, waste, vent), electrical conduit and sewer / drain applications.

1124 is manufactured to the high standard of ASTM D 3138 to ensure a quality product. A sample is kept from each batch to verify the quality of Arrow cements. This product is manufactured in the U.S.A.


Follow the directions on can label. Additional information is available upon request. Skill and knowledge on the part of the user is required to make a good quality joint.

SAFETY PRECAUTIONS

EXTREMELY FLAMMABLE. Do not use or store near heat, sparks or flame. Use only in well ventilated area. Keep container closed when not in use. Avoid prolonged breathing of vapor. Avoid contact with skin and eyes. In case of skin or eye contact, flush repeatedly with water. Get medical attention if irritation persists. If swallowed, drink water, do NOT induce vomiting and call a physician. Keep out of reach of children.

TECHNICAL DATA

<u>PRODUCT</u>	<u>BODY</u>	<u>COLOR</u>	<u>DENSITY</u>	<u>SET TIME</u>
1124	Medium	Clear or Green	7.6 lb/gal	Fast

- MAX VOC PER SCAQMD 1168/316A: 510 G/L
- SPECIFICATIONS: ASTM D 3138, SCAQMD 1168/316A
- HYDROSTATIC PRESSURE TEST: 400 psi min. (73° F, 2 hour cure)
- FLASH POINT: -4° F (closed cup)
- SHELF LIFE: 3 year minimum
- LISTINGS: NSF (National Sanitation Foundation) 
- U.P. Code (Uniform Plumbing Code)