

5457 Spalding Dr. Norcross, GA 30092 770-448-9058 Fax 770-449-1361 www.arrowadhesives.com

## **PRODUCT DATA SHEET**

# 1126RB

PVC Regular Body Cement

#### **DESCRIPTION**

1126RB is a low VOC emission, PVC solvent cement designed specifically for use in joining all PVC electrical duct and conduit pipe and fittings with interference fit through 4" diameter. It is a clear, regular body, fast setting, high strength PVC Cement. This product can be used with or without Primer; check local code requirements.

#### **APPLICATION**

1126RB is formulated for use on all PVC duct and conduit applications through 4" diameter. 1126RB is manufactured to the high standard of ASTM D 2564 to ensure a quality product. A sample is kept from each batch to verify the quality of *Arrow* cements. This product is manufactured in the U.S.A.

Do not use ARROW solvent cements in a compressed air / gas system.

#### **CERTIFICATION LISTINGS**

- Meets ASTM D 2564 Performance Standard
- Meets requirements of Underwriters Laboratories UL-651 and National Electrical Manufacturers Association (NEMA) TC-2, TC-6 and TC-8
- Meets SCAQMD 1168/316A. LEED Compliant and credit can be claimed for LEED Green Building Rating System – Indoor Environmental Quality

### **SAFETY PRECAUTIONS**

EXTREMELY FLAMMABLE. Do not use or store near heat, sparks or flame. Use only in well ventilated area. Keep container closed when not in use. Avoid prolonged breathing of vapor. Avoid contact with skin and eyes. In case of skin or eye contact, flush repeatedly with water. Get medical attention if irritation persists. If swallowed, drink water, do NOT induce vomiting and call a physician. Keep out of reach of children. Follow the directions on can label. This product is flammable and considered a hazardous material. Carefully read Material Safety Data Sheet and follow all precautions. Skill and knowledge on the part of the user is required to make a quality joint. Do not use this product for other than intended use.

#### **TECHNICAL DATA**

<u>PRODUCT</u>	<b>BODY</b>	<u>COLOR</u>	<b>DENSITY</b>	SET TIME	Shelf-life
1126RB	Regular	Clear	7.5 lb/gal	Fast	3 Years
Product Number		<u>Size</u>	<b>Packing</b>	Carton Weight	
1126RB-4		4 oz.	24 / carton	7 lbs.	
1126RB-2		8 oz.	24 / carton	13 lbs.	
1126RB-P		16 oz.	12 / carton	14 lbs.	
1126RB-Q		32 oz.	12 / carton	27 lbs.	
1126RB-G		128 oz.	6 / carton	52 lbs.	

SPECIALISTS IN SOLVENT CEMENT AND ADHESIVES