



**PRODUCT DATA SHEET**

**911**  
**PRIMER**

**DESCRIPTION**

911 is a solvent primer for priming PVC and CPVC plastic pipe and fittings. Tests have shown that greater long-term joint strength is obtained with the use of a primer. Primer cleans, softens and dissolves the surface of the pipe and fitting, thus providing better bonding surfaces for the solvent cement when it is applied. 911 meets 'LOW-VOC' requirements, as outlined by SCAQMD 1168/316A.

**APPLICATION**

911 Primer is recommended for pressure applications. Additional applications include potable water, DWV (drain, waste, vent), conduit, irrigation and sewer systems.

911 is manufactured to the high standard of ASTM F 656 to ensure a quality product. A sample is kept from each batch to verify the quality of Arrow products.

Follow the directions on can label. Additional information is available upon request. Skill and knowledge on the part of the user is required to make a good quality joint.

**SAFETY PRECAUTIONS**


HIGHLY FLAMMABLE. Do not use or store near heat, sparks or flame. Use only in well ventilated area. Keep container closed when not in use. Avoid prolonged breathing of vapor. Avoid contact with skin and eyes. In case of skin or eye contact, flush repeatedly with water. Get medical attention if irritation persists. If swallowed, drink water, do NOT induce vomiting and call a physician. Keep out of reach of children.

**TECHNICAL DATA**

<u>PRODUCT</u>	<u>COLOR</u>	<u>DENSITY</u>	<u>VISCOSITY</u>
911	Clear or Purple	7.1 lb/gal	Water-thin

MAX VOC PER SCAQMD 1168/316A: 550 G/L  
SPECIFICATIONS: ASTM F 656, SCAQMD 1168/316

FLASH POINT: 6° F (closed cup)

LISTINGS: NSF (National Sanitation Foundation)   
U.P. Code (Uniform Plumbing Code)