



5457 Spalding Dr. Norcross, GA 30092 770-448-9058 D Fax 770-449-1361 www.arrowadhesives.com

PRODUCT DATA SHEET

WHITE PTFE SEALANT

DESCRIPTION

A-10 is an industrial strength thread sealant that includes a higher concentration of PTFE resins which provides for greater sealing power and produces a leak proof seal on all types of metal and plastic threaded connections. A-10 will not harden or dry out over time and remains flexible for easy disassembly. It is non-toxic, is easy to clean-up and will stick to hot oily threads.

APPLICATION

A-10 can be applied to all types of pipe threads including steel, brass, aluminum, iron and PVC, ABS and CPVC plastic. A-10 is recommend for use on water, steam, air, natural gas, refrigerants and ammonia service. It is not for use on oxygen service.

A-10 has a temperature range from -50F to 500F; and pressure range up to 1,500 psi for gas and up to 5,000 psi for liquid.

Use A-10 as supplied in its original container. Stir well before using. Brush liberally onto make threads. Make up joint in normal manner. A brush cap is included in each can.

TECHNICAL DATA

PRODUCT BODY COLOR DENSITY A-10 White 10.9 lb/gal Paste

SPECIFICATIONS: Meets TT-S-1732

SHELF LIFE: 1 year minimum

NSF (National Sanitation Foundation) LISTINGS: